

Рассеиваемая мощность

Мощность [Вт/полюс]	T1/T1 1p	T2		T3		T4		T5		
	In[A]	F	F	P	F	P	F	P/W	F	P/W
TMD	1		1.5	1.7						
TMA	1.6		2.1	2.5						
TMG	2		2.5	2.9						
MF	2.5		2.6	3						
MA	3.2		2.9	3.4						
	4		2.6	3						
	5		2.9	3.5						
	6.3		3.5	4.1						
	8		2.7	3.2						
	10		3.1	3.6						
	12.5		1.1	1.3						
	16	1.5	1.4	1.6						
	20	1.8	1.7	2			3.6	3.6		
	25	2	2.3	2.8						
	32	2.1	2.7	3.2			3.7	3.7		
	40	2.6	3.9	4.6						
	50	3.7	4.3	5			3.9	4.1		
	63	4.3	5.1	6	4.3	5.1				
	80	4.8	6.1	7.2	4.8	5.8	4.6	5		
	100	7	8.5	10	5.6	6.8	5.2	5.8		
	125	10.7	12	14.7	6.6	7.9	6.2	7.2		
	160	15	17	20	7.9	9.5	7.4	9		
	200				13.2	15.8	9.9	12.4		
	250				17.8	21.4	13.7	17.6		
320						20.6	27	13.6	20.9	
400								19.5	31	
500								28.8	36.7	
630								44	56.6	
PR221-222	10		0.5	0.6						
	25		1	1.2						
	63		3.5	4						
	100		8	9.2			1.7	2.3		
	160		17	20			4.4	6		
	250						10.7	14.6		
	320						17.6	24	10.6	17.9
	400								16.5	28
630								41	53.6	